

MACHINE GALAXY -DOOR

WRAPPING MACHINE WITH STRETCH FILM FOR DOORS AND WINDOWS

SPECIFICATIONS

- Pressing arm with fork support for doors/windows
- Bottom frame with fork supports for doors/windows
- Pedal switch for pressing arm control
- display touch screen 7" color
- machine controlled by PLC
- siemens frequency converters on all the motors
- machine power 1,75 kw
- machine supply 220-240 VAC 1 ph, 50-60 Hz
- turntable diameter 1650 mm ( max pallet 1200x100 mm )
- max pallet weight 2100kg
- Beeper on cycle start
- table phase stop
- height sensing with photocell
- height also settable by the panel
- n° 99 custom programs
- upward speed adjust
- downward speed adjust
- speed rotation adjust
- management of the film tension and percentage of pre-stretch

GALAXY-DOOR



bottom rounds adjust

top rounds adjust

photocell delay adjust

only up cycle

only down cycle

up and down cycle

up and down cycle alternate

cycle with reinforcement at pre-set height

cycle with start at pre-set height

top sheet cycle

possibility to set a protection password on parameters

machine diagnostic by display

available wrapping heights:

2400 = H 2400 mm (with film coil h500 mm )

2800 = H 2800 mm (with film coil h500 mm )

3200 = H 3200 mm (with film coil h500 mm )

available film coil carriages:

FE : electromagnetic brake and film tension adjust by control panel

PM : power pre-stretch fix 230% (other on demand) and film tension adjust by control panel

PMV : power pre-stretch adjustable up to 230% (other on demand). Separated adjust of tension and pre-stretch by control panel

